

# Technical Test Theory

## Crane/Lifting Operations Supervisor A62



No.	Question
1	What advantage is there in increasing the number of falls on a hook block?
2	Name TWO possible penalties for not following legal requirements when using a crane.
3	If a heavy load is being slewed at too a high speed over at least 180 degrees, what TWO factors must the operator and signaller take into account?
4	Explain the purpose of the over-hoist limit switch.
5	Name THREE ways that a crane supervisor can contribute in ensuring repeat business with the client or principal contractor.
6	To whom should the appointed person give all details involving the lifting operation?
7	The operator has to use a new model of crane that they are unfamiliar with. What do Regulations (i.e. LOLER 98) and other guidance require the operator to have?
8	If setting up to lift loads near a pedestrianised area, what main factor needs to be taken into account?
9	List SIX typical subject areas that should be covered in a site induction.
10	How can a qualification or card benefit a crane supervisor?
11	State SIX environmental factors that can affect an external lifting operation.
12	State why there must be a safe system of work.

# Technical Test Theory

## Crane/Lifting Operations Supervisor A62



No.	Question
13	Give THREE examples of how excessive rain can affect an external lifting operation when using a mobile crane.
14	What are the types of warning that an RCI will indicate?
15	Name THREE factors that determine the safe working load of the crane.
16	List TWO methods of obtaining the accurate weight of a load.
17	What is the purpose of a risk assessment?
18	What are the possible outcomes if facing prosecution for not complying with legislation and regulations?
19	a) What is meant by the lifting capacity of the crane and b) who determines it?
20	Name FOUR different types or levels of disciplinary actions or sanctions that can be applied (by employers and judicial bodies) to operators of plant who do not comply with, or follow legislation and regulations.
21	How is the SWL/WLL/rated capacity for multi-leg slings determined?
22	a) What is the purpose of a Method Statement and b) what is required of the operator?
23	What is the minimum recommended distance that is allowed between the counterweight(s) of the crane and another object/structure?
24	State the safe procedure to be followed before lifting or lowering a load down a shaft or excavation.

# Technical Test Theory

## Crane/Lifting Operations Supervisor A62



No.	Question
25	How long is a thorough examination for a lifting accessory valid for?
26	Name a design of accessory hook that is exempt from being fitted with a safety catch.
27	Identify FOUR requirements for ensuring the stability of mobile cranes on site.
28	What is the maximum angle that a bow shackle used as a pair on a crane hook can be used at?
29	What are the THREE actions or stages that a crane operator undertakes during pre-use inspections?
30	Name TWO duties of the crane operator.
31	What is the definition of, or how can a hazard be described?
32	What do The Work at Height Regulations require of crane supervisors?
33	Define the term 'radius'.
34	Name FOUR items that must be recorded when a thorough examination on a lifting appliance has been carried out.
35	If radios are to be used during the lifting operations, what FIVE actions and checks must be made before use?
36	Explain the difference between an employing and user organisation.

# Technical Test Theory

## Crane/Lifting Operations Supervisor A62



No.	Question
37	In which applications are single-leg slings rated with their SWL (WLL)?
38	How does the deflection of the boom on a mobile crane or jib affect the lift?
39	Two cranes are working in the same vicinity that encroach the operating radius of each. What actions would the lift plan or method statement normally specify?
40	A tower crane has been delivered to site, assembled and configured for lifting. What must be carried out before lifting starts and by whom?
41	a) On a tower crane, where must the load radius diagram be located and b) what information must it contain?
42	Where should the crane's Operator's Manual be kept and why?
43	State the maximum recommended angle for single-leg slings when used as a pair.
44	When a crane company hires out a crane, name TWO main legal requirements the hire company must meet regarding the crane and driver.
45	What does The Health and Safety at Work Act require employers to do with regards specifically to plant?
46	If a crane is out of level, what effect will it have on the radius?
47	Name THREE ways in which an operator can minimise their impact upon the environment whilst using a crane.
48	a) What determines the minimum distances that any part of plant and machinery has to be kept from over head electricity lines and b) explain why a distance should be kept.

# Technical Test Theory

## Crane/Lifting Operations Supervisor A62



No.	Question
49	Why must a crane driver never try and 'drag' a load?
50	Which part of BS 7121 is specific to mobile cranes?
51	Who has overall control of the lifting operation?
52	What is the difference between a contract lift and a 'standard' crane hire?
53	During the lifting operation, part of the task cannot be carried out as detailed in the lift plan. a) What initially must happen to the lifting operation and b) who authorises any changes?
54	A replacement crane driver has been supplied to continue the lift. What must they be made aware of before further lifting can take place?
55	Name FIVE requirements that must be followed if accessing the end of the jib for maintenance purposes.
56	Who is responsible for providing the contractor with written details of the work to be done?
57	According to BS 7121 Part 1: a) what is the minimum number of allowable turns on the hoist drum and b) who decides the actual minimum for a given model of crane?
58	What THREE main duties of The Health and Safety at Work Act must employees follow?
59	What is the 'Factor of Safety' when lifting personnel?
60	What is the meaning of this hand signal (being demonstrated by the Tester)?

# Technical Test Theory

## Crane/Lifting Operations Supervisor A62



No.	Question
61	To lift a load of 12 tonnes on a two-point lift using single-leg slings, what is the required SWL (WLL) for each sling with an included angle of 87 degrees? Please explain your calculation.
62	List FOUR items to be found on a chain sling inspection certificate.
63	If the operator has to leave the cab of a crane for a short period, state at least TWO actions that must be taken before they leave.
64	Give TWO methods of obtaining the centre of gravity on an unbalanced load.
65	Why is it important to ensure the wheels are clear of the ground when outriggers are employed?
66	If a mobile crane on blocked duties is slewing through 180 degrees and is unladen, what can cause a change of ground loading in each stabiliser.
67	a) When and b) why are axle or suspension locks fitted to most mobile cranes?
68	Describe how to calculate the area of support beneath a crane outrigger, which gives maximum possible safeguards against ground subsidence.